


4900 HI

Sliding

Standard sliding system with hinged features. Offers great thermal and acoustic performance favoured by a glazing capacity of up to 36 mm and a thermal break zone of 34 mm. It has an interlock section of 35 mm and straight lines, allowing the sashes to cross over thanks to the integrated handle with multilock system.



OPENING POSSIBILITIES




Sliding
1 rail (sash + fixed light)
2 and 3 rails
Pocket possibility
Possibility of 90° opening without mullion

Sliding
Thermally broken

POSSIBILITIES



ACCESSIBILITY



FEATURES

Transmittance		$U_w \geq 1.2$ (W/m ² K)
Acoustic insulation		Rw up to 40 dB
Air permeability		Class 4
Watertightness		Class 7A
Wind resistance		Class CS

Reference (ed. 1.80 x 2.20 m / 2 sashes)

- Sighelines**
Frame 60, 70, 89, 120, 125, 130 mm
126, 145 mm 3 rails
201 mm 4 rails
Sash 48 mm
- Polyamide Strip Length**
34 mm
- Profile Thickness**
Window 1,6 mm
- Glazing**
Max. 36 mm, Min. 24 mm
- Maximum Sash Dimensions**
Width (L) 2200 mm
Height (H) 3000 mm
- Maximum Sash Weight**
240 kg

Consult maximum weight and dimensions according to typologies



4900 HI SLIDING