

COR VISION

Plus


The greatness of minimalism is reflected in this sliding system of large dimensions with sashes of up to 4 meters, interlock sightline of only 25 mm and frames embedded in the perimeter, allowing for a glazed surface of up to 94%. It has a maximum glazing capacity of 56 mm, offering excellent thermal and acoustic performances. Available with manual (up to 400 kg) or motorized (up to 700 kg) opening system. Additionally, accessibility is favoured by the possibility of hiding the rail and even integrating it fully into the floor.

FEATURES

Transmittance		Uw ≥ 0.9 (W/m²K)
Acoustic insulation		Rw up to 43 dB
Air permeability		Class 4
Watertightness		Class 7A* / 9A**
Wind resistance		Class C3* / C4**

Wind resistance:
 * Reference test balcony 4.00 x 3.00 m / 2 sashes
 ** Reference test balcony 4.00 x 3.00 m / 1 sash + 1 fixed light

OPENING POSSIBILITIES



Sliding
 Possibility of 1, 2, 3 or 4 rails
 Possibility of inner and outer corner sash at 90° without mullion
 Pocket possibility

Sliding
 Thermally broken



Sightlines

Frame 180 mm / 278 mm 3 rails
 Sash 69 mm

Polyamide Strip Length

Frame 40 mm
 Sash 18 / 32 mm

Profile Thickness

Door 2.0 mm

Glazing

Max. 56 mm, Min. 36 mm

Maximum Sash Dimensions

Width (L) 4000 mm, Height (H) 4000 mm
 *Glazed surface 34 m²

Maximum Sash Weight

400 kg Manual
 700 Kg Motorized

Consult maximum weight and dimensions according to typologies

